

MGD2103SV un uleu FULL HD 1080P Star Ea/Ly DWDR H265 POE ((L)) light HD 1080P H.265 EaZv DWDR PoE Mobile Starlight Networking Surveillance


H.265 2MP Starlight IR Bullet IP Camera

FEATURES

- Free P2P Cloud Networking
 - -- **Cloud Networking** available to connect this device to Internet automaticallyin three steps with our free mobile app.
 - -- The **Buddy** feature to share the device access permission to other people.
 - -- Device login / out notifications reported.




- Starlight visibility to offer clear & color images even at night
- **DIMENSIONS**



- POE (Power-over-Ethernet) support to eliminate the use of power cables and reduce installation costs
- ONVIF (OnVIFS) standard supported to simplify system integration
- Vertical View Mode supported to monitor long and narrow areas such as corridors and aisles.
- Remote Surveillance
 - -- Fully compatible with iOS and Android devices, and Internet Explorer on Windows operating system

-- Free PC program, **CMS Lite**, for 32CH devices monitoring on Windows operating system





SPECIFICATIONS

LAN Port	YE	S	
LAN Speed	10/100 Based	10/100 Based-T Ethernet	
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSF RTCP,IPv4/IPv6, Bonjour, UPnP, DNS,UDP,IGMP, QoS, SNMP		
ONVIF Compatible	YES (Profile S)		
Number of Online Users	10		
Security	(1) Multiple user access levels with password(2) IP address filtering		
Remote Access	 (3) Digest authentication (1) Internet Explorer on Windows operating system (2) CMS Lite, 32CH CMS software for Windows operating system (3) iOS & Android mobile devices 		
Video			
Network Compression	H.265 / H.264 / MJPEG		
Video Resolution	1920 x 1080 / 1280 x 720 / 720 x 480 / 352 x 240		
Frame Rate	30fps		
Multiple Video Streaming	4 (H.265 / H.264 / MJPEG)		
General			
Image Sensor	1/2.8" CMOS	image sensor	
Min Illumination	0.001 Lux / F1.6, 0 Lux (IR LED ON)		
Shutter Speed	1/2 to 1/10,000 sec		
S/N Ratio	More than 48dB (AGC off)		
Lens	f3.6mm / F1.6	f2.8mm / F1.6	
Viewing Angle	84° (Horizontal) / 45° (Vertical) / 99° (Diagonal)	101° (Horizontal) / 54° (Vertical) / 120° (Diagonal)	
IR LED	2 Units		
IR Effective Distance**	Up to 25 meters		
IR Shift	YES		
Smart Light Control	YES		
White Balance	ATW		
AGC	Auto		
IRIS Mode	AES		
Sharpness	YES		
DWDR	YES		
POE	YES (IEEE 802.3af)		
Privacy Mask	YES		
Vertical View Mode	YES		
Weather-proof	IP66		
Operating Temperature	-25°C ~ 50°C		
Operating Humidity	90 or less relative humidity		
Power Source (±10%)	12V / 1A 140m4 (IP LED OEE) / 220m4 (IP LED ON)		
Current Consumption (±10%)	140mA (IR LED OFF) / 220mA (IR LED ON) PoE & PoN: 3.7W; DC adapter: 3W		
Power Consumption (±10%)	POE & PON: 3.7W	0.36	



SPECIFICATIONS (CONTINUED)

EaZy Networking	YES	
Mobile Surveillance	iOS & Android mobile devices	
Motion Detection	YES	
Event Notification	FTP / Email / SMS	
RTC (real-time clock)	YES	
Digital Pan / Tilt / Zoom	YES	
Minimum Web Browsing Requirements	 Intel core i3 or higher, or equivalent AMD 2GB RAM AGP graphics card, Direct Draw, 32MB RAM Windows 10, Windows 8, Windows 7, Windows Vista & Windows XP, DirectX 9.0 or late Internet Explorer 7.x or later (Windows Edge not supported) 	
Optional Junction Box	WVA456-WBKT / WVA456- WHKT	
Certification	CE	

*The specifications are subject to change without notice.